

View Online at <https://aerobasegroup.com/nsn/5950-01-234-8278>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.750 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.500 inches single mounting facility single center group

**Frequency Rating:**

55.0 hertz single component and 65.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield grounded to terminal single component

**Body Length:**

5.500 inches

**Body Width:**

4.750 inches

**Body Height:**

3.500 inches

**Maximum Operating Temp:**

85.0 degrees celsius

**Inclosure Type:**

Hermetically sealed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded hole single group

**Winding Function And Quantity:**

1 primary single component and 6 secondary single component

**Thread Size:**

0.250 inches single group

**Winding Operating Current:**

3.5 amperes ac single component 1st secondary

**Winding Operating Voltage:**

35.60 ac volts single component 1st secondary

**Special Features:**

1primary winding; 6secondary windings

**Precious Material And Location:**

Terminals gold

**Precious Material:**

Gold

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

15 solder stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0