

View Online at <https://aerobasegroup.com/nsn/5950-01-235-6253>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

19.9 millimeters single mounting facility all center groupings and 20.1 millimeters single mounting facility all center groupings

Center To Center Distance Between Mounting Facilities Parallel To Width:

7.9 millimeters single mounting facility all center groupings and 8.1 millimeters single mounting facility all center groupings

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Core Construction:

Solid single component

Body Length:

Between 35.0 millimeters and 37.0 millimeters

Body Width:

Between 19.0 millimeters and 21.0 millimeters

Body Height:

Between 25.0 millimeters and 27.0 millimeters

Winding Quantity:

1 single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 all groupings

Mounting Method:

Threaded hole all groupings

Rating Method:

Electrical single component single winding

Thread Size:

6.0 millimeters all groupings

Winding Conductor Size:

0.02010 inches american wire gage single component single winding

Winding Operating Current:

255.0 milliamperes ac single component single winding

Dc Resistance Rating In Ohms:

47.000 single component single winding

Winding Operating Voltage:

12.00 ac volts single component single winding

Thread Series Designator:

M all groupings

Terminal Type And Quantity:

1 connector, plug and 1 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0