## NSN 5950-01-235-6695

Reactor-transformer - Page 1 of 2



view Online at https://aerobasegroup.com/nsn/5950-01-255-6695
Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.825 inches single mounting facility single center group
Inductance Rating:
50.00 microhenries 2nd component single winding and 140.00 microhenries 2nd component single winding
Frequency Rating:
400.0 hertz 2nd component
Input-output Phase Relationship:
Single phase to single phase 1st component
Body Length:
1.265 inches
Body Width:
1.265 inches
Body Height:
1.500 inches
Distance Between Mounting Facility Centers:
0.825 inches single mounting facility single center group
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
2 single group
Mounting Method:
Threaded hole all groupings
Rating Method:
Electrical 1st component single primary output
Winding Function And Quantity:
1 primary, variable autotransformer type 1st component
Thread Size:
0.112 inches single group
Winding Operating Current:
4.5 amperes dc 2nd component single winding and 10.5 amperes dc 2nd component single winding
Dc Resistance Rating In Ohms:
1.350 1st component single primary output
Thread Series Designator:
Unc single group
Terminal Type And Quantity:
8 wire hook
Shelf Life:
N/a
Unit Of Measure:

## NSN 5950-01-235-6695

Reactor-transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0