NSN 5950-01-235-6697

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-235-6697

lot established	
Overall Length:	
.250 inches	
center To Center Distance Between Mounting Facilities Parallel To Le	nath:
.750 inches single mounting facility single center group	ngun.
Center To Center Distance Between Mounting Facilities Parallel To Wi	dth:
.000 inches single mounting facility single center group	utii.
Overall Height:	
.000 inches	
Overall Width:	
.250 inches	
requency Rating:	
00.0 hertz single component	
nput-output Phase Relationship:	
hree phase to three phase single component	
ransformer Winding Connection Type:	
Delta-wye	
Vinding Shielding Method:	
nternal shield grounded to inclosure and core single component	
laximum Operating Temp:	
5.0 degrees celsius	
nclosure Type:	
Open	
lounting Facility Quantity:	
single group	
lounting Method:	
hreaded hole single group	
Vinding Function And Quantity:	
primary single component and 3 secondary single component	
hread Size:	
.190 inches single group	
Vinding Power Rating:	
50.0 volts-amperes single component 1st secondary	
Vinding Operating Voltage:	
16.00 ac volts, single component single primary	

416.00 ac volts single component single primary

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

21 tab, solder lug

Shelf Life:

N/a

NSN 5950-01-235-6697

Power Transformer - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A058b0