## NSN 5950-01-235-7768

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-235-7768

## **Reliability Indicator:**

Not established

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

2.125 inches single mounting facility single center group

#### **Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.125 inches single mounting facility single center group

#### **Overall Height:**

3.207 inches

#### **Overall Width:**

3.207 inches

#### Frequency Rating:

400.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

#### **Winding Shielding Method:**

Internal shield brought out to terminal single component

#### **Body Length:**

2.947 inches

#### **Inclosure Type:**

Fully enclosed

## **Mounting Facility Quantity:**

2 single group

#### **Mounting Method:**

Threaded hole single group

#### **Winding Function And Quantity:**

1 primary single component and 10 secondary single component

## Thread Size:

0.164 inches single group

## **Winding Operating Current:**

3.0 milliamperes ac single component single primary

#### **Winding Operating Voltage:**

37.12 ac volts single component 4th secondary

#### **Special Features:**

One primary and ten secondaries, with first through ninth secondary center tapped

#### **Thread Series Designator:**

Unc single group

#### **Terminal Type And Quantity:**

32 turret

#### **Specification Data:**

88818-a504a415-101 manufacturers source control

## Shelf Life:

N/a

# NSN 5950-01-235-7768

Power Transformer - Page 2 of 2



**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A058b0