

View Online at <https://aerobasegroup.com/nsn/5950-01-237-7957>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

Between 0.595 inches and 0.781 inches

Mounting Hole Diameter:

0.146 inches single group and 0.166 inches single group

Inductance Type:

Fixed

Inductance Rating:

350.00 microhenries single component single winding

Frequency Rating:

10.0 kilohertz single component

Overall Diameter:

Between 0.845 inches and 0.905 inches

Maximum Operating Temp:

130.0 degrees celsius

Winding Quantity:

1 single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

1 single group

Mounting Method:

Unthreaded hole single group

Rating Method:

Electrical single component single winding

Winding Operating Current:

2.2 amperes dc single component single winding

Dc Resistance Rating In Ohms:

0.200 single component single winding

Test Data Document:

81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 pin

Specification Data:

81349-mil-t-27/287 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0