

View Online at <https://aerobasegroup.com/nsn/5950-01-237-7964>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.688 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.438 inches single mounting facility single center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

15.4 volt-ampere single component

Winding Shielding Method:

Internal shield grounded to core and brought out to terminal single component

Body Length:

Between 2.187 inches and 2.312 inches

Body Width:

Between 1.937 inches and 2.062 inches

Body Height:

Between 2.937 inches and 3.125 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

1.19 amperes ac single component all secondary

Winding Power Rating:

7.7 volts-amperes single component all secondary

Winding Operating Voltage:

6.12 ac volts single component all secondary and 6.49 ac volts single component all secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

7 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0