

View Online at <https://aerobasegroup.com/nsn/5950-01-239-1949>

Reliability Indicator:

Not established

Overall Length:

1.750 inches

Overall Height:

1.000 inches

Overall Width:

1.250 inches

Mounting Hole Diameter:

0.120 inches single group and 0.130 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Maximum Operating Temp:

130.0 degrees celsius

Distance Between Mounting Facility Centers:

1.344 inches single mounting facility single center group and 1.406 inches single mounting facility single center group

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

5.0 milliamperes ac single component single secondary

Winding Power Rating:

0.025 volts-amperes single component single secondary

Winding Operating Voltage:

5.00 ac volts single component single secondary

Test Data Document:

21877-174100 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

5 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0