# NSN 5950-01-239-7843

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-239-7843

# **Reliability Indicator:**

Not established

## Center To Center Distance Between Mounting Facilities Parallel To Length:

1.125 inches single mounting facility single center group

## Center To Center Distance Between Mounting Facilities Parallel To Width:

1.875 inches single mounting facility single center group

#### **Frequency Rating:**

60.0 hertz single component

#### Input-output Phase Relationship:

Single phase to single phase single component

## Maximum Transformer Power Rating:

250.0 milliwatts single component

## Winding Shielding Method:

Internal shield grounded to inclosure single component

## **Body Length:**

## 2.375 inches

**Body Width:** 

1.630 inches

#### Body Height:

1.630 inches

## Maximum Operating Temp:

130.0 degrees celsius

## Inclosure Type:

Fully enclosed

## **Mounting Facility Quantity:**

4 single group

## **Mounting Method:**

Threaded hole single group

## Winding Function And Quantity:

1 primary single component and 2 secondary single component

## Thread Size:

0.138 inches single group

## Winding Operating Current:

10.0 milliamperes ac single component single primary

## Winding Operating Voltage:

21.00 ac volts single component 2nd secondary

## **Thread Series Designator:**

Unc single group

## **Terminal Type And Quantity:**

6 solder stud

#### Shelf Life:

N/a

# NSN 5950-01-239-7843

Power Transformer - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A058b0

