

View Online at <https://aerobasegroup.com/nsn/5950-01-239-7982>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.500 inches 2nd mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.980 inches 2nd mounting facility single center group and 2.020 inches 2nd mounting facility single center group

Mounting Slot Width:

0.183 inches 1st group and 0.193 inches 1st group

Frequency Rating:

55.0 hertz single component and 65.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

126.5 volt-ampere single component

Winding Shielding Method:

Internal shield grounded to inclosure and core single component

Body Length:

Between 8.060 inches and 8.120 inches

Body Width:

Between 2.690 inches and 2.750 inches

Body Height:

3.000 inches

Maximum Operating Temp:

95.0 degrees celsius

Distance Between Mounting Facility Centers:

1.980 inches 1st mounting facility single center group and 2.020 inches 1st mounting facility single center group

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 2nd group

Mounting Method:

Threaded hole 2nd group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.138 inches 2nd group

Winding Operating Current:

1.1 amperes ac single component single secondary

Winding Operating Voltage:

115.00 ac volts single component single secondary

Thread Series Designator:

Unc 2nd group

Terminal Type And Quantity:

3 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0