## NSN 5950-01-240-4209

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-240-4209

## **Reliability Indicator:** Not established **Mounting Hole Diameter:** 0.146 inches single group and 0.166 inches single group Inductance Type: Fixed Inductance Rating: 220.00 microhenries single component all winding **Frequency Rating:** 10.0 kilohertz single component **Body Length:** Between 0.625 inches and 0.751 inches **Body Outside Diameter:** Between 1.158 inches and 1.218 inches Maximum Operating Temp: 130.0 degrees celsius Winding Quantity: 2 single component Inclosure Type: Fully enclosed **Mounting Facility Quantity:** 1 single group **Mounting Method:** Unthreaded hole single group **Rating Method:** Electrical single component all winding Winding Operating Current: 4.5 amperes dc single component all winding **Dc Resistance Rating In Ohms:** 0.080 single component all winding **Test Data Document:** 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 4 pin **Specification Data:** 81349-mil-t-27/288 government specification Shelf Life: N/a

Unit Of Measure:

--

Demilitarization:

No

## NSN 5950-01-240-4209

Reactor - Page 2 of 2

Fiig: A058b0

