

View Online at <https://aerobasegroup.com/nsn/5950-01-240-7949>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.188 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.938 inches single mounting facility single center group

Overall Width:

3.630 inches

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Three phase to single phase single component and three phase to three phase single component

Transformer Winding Connection Type:

Wye-wye

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

3.630 inches

Body Width:

3.380 inches

Body Height:

2.000 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 7 secondary single component

Thread Size:

0.164 inches single group

Winding Operating Current:

1.5 amperes dc single component 2nd secondary

Winding Operating Voltage:

33.00 dc volts single component 2nd secondary

Special Features:

Three secondaries share a neutral tap; also, item comprised of one primary winding; seven secondary windings, with fifth and sixth secondaries center tapped

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

39 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0