# NSN 5950-01-241-9802

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-241-9802

# Reliability Indicator:

Not established

# **Overall Length:**

13.600 inches

# Center To Center Distance Between Mounting Facilities Parallel To Length:

7.740 inches single mounting facility single center group

# Center To Center Distance Between Mounting Facilities Parallel To Width:

5.500 inches single mounting facility single center group

### **Overall Height:**

11.400 inches

### **Overall Width:**

11.900 inches

### Mounting Slot Width:

0.562 inches single group

### Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

# Input-output Phase Relationship:

Single phase to single phase single component

# Maximum Transformer Power Rating:

9.85 kilovolt-ampere single component

# Winding Shielding Method:

Internal shield brought out to terminal single component

# Inclosure Type:

Partially enclosed

# **Mounting Facility Quantity:**

12 single group

# **Mounting Method:**

Bracket single group and slot single group

# Winding Function And Quantity:

2 primary single component and 2 secondary single component

# Winding Operating Current:

60.0 amperes dc single component 2nd secondary

# Winding Operating Voltage:

95.00 ac volts single component 2nd secondary

# **Terminal Type And Quantity:**

11 screw

Shelf Life:

N/a

Unit Of Measure:

--

# Demilitarization:

No

# NSN 5950-01-241-9802

Power Transformer - Page 2 of 2

**Fiig:** A058b0

