NSN 5950-01-242-4434

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-242-4434

Reliability Indicator:

Not established

Frequency Rating:

50.0 hertz single component and 400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internally shielded and brought out to primary terminal single component

Body Length:

3.850 inches

Body Width:

5.400 inches

Body Height:

5.500 inches

Inclosure Type:

Fully enclosed

Mounting Method:

Terminal single group

Winding Function And Quantity:

2 primary single component and 15 secondary single component

Winding Operating Current:

1.0 amperes ac single component 1st secondary

Winding Operating Voltage:

100.00 ac pounds per hour wet single component all primary and 110.00 ac pounds per hour wet single component all primary and 120.00 ac pounds per hour wet single component all primary and 200.00 ac pounds per hour wet single component all primary and 240.00 ac pounds per hour wet single component all primary and 240.00 ac pounds per hour wet single component all primary and 240.00 ac pounds per hour wet single component all primary and 240.00 ac pounds per hour wet single component all primary

Terminal Type And Quantity:

39 wire lead

Shelf Life:

N/a

Unit Of Measure:

```
--
```

Demilitarization:

No

Fiig:

A058b0