NSN 5950-01-242-5692

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-242-5692

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.800 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.120 inches single mounting facility single center group

Mounting Hole Diameter:

0.180 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

244.3 volt-ampere single component

Winding Shielding Method:

Internal shield grounded to core single component and internal shield grounded to inclosure and secondary center tap single component

Body Length:

3.300 inches

Body Width:

2.590 inches

Body Height:

2.350 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 4 secondary single component

Winding Operating Current:

3.89 amperes ac single component 2nd secondary

Winding Power Rating:

32.2 volts-amperes single component 1st secondary

Winding Operating Voltage:

39.00 ac volts single component 2nd secondary

Special Features:

Two shields

Terminal Type And Quantity:

12 tab, solder lug

Shelf Life:

N/a

NSN 5950-01-242-5692

Power Transformer - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A058b0