

View Online at <https://aerobasegroup.com/nsn/5950-01-242-9364>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.250 inches single mounting facility single center group

Mounting Hole Diameter:

0.196 inches single group

Mounting Slot Width:

0.196 inches single group

Frequency Rating:

400.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

246.5 volt-ampere single component

Body Length:

3.125 inches

Body Width:

3.000 inches

Body Height:

3.750 inches

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group or unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Winding Operating Current:

6.3 amperes ac single component 2nd secondary

Winding Power Rating:

79.5 volts-amperes single component 1st secondary

Winding Operating Voltage:

26.50 ac pounds per hour wet single component all secondary

Terminal Type And Quantity:

6 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0