

View Online at <https://aerobasegroup.com/nsn/5950-01-243-0648>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.380 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.940 inches single mounting facility single center group

Mounting Hole Diameter:

0.184 inches single group and 0.190 inches single group

Frequency Rating:

55.0 hertz single component and 65.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield grounded to inclosure and core and brought out to terminal single component

Body Length:

4.060 inches

Body Width:

2.000 inches

Body Height:

3.380 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

0.75 amperes dc single component single secondary

Winding Operating Voltage:

31.00 ac pounds per hour wet single component single secondary

Terminal Type And Quantity:

5 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0