

View Online at <https://aerobasegroup.com/nsn/5950-01-244-0514>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.590 inches single mounting facility single center group and 0.610 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.390 inches single mounting facility single center group and 0.410 inches single mounting facility single center group

Inductance Rating:

0.80 millihenries single component single primary and 1.20 millihenries single component single primary

Frequency Rating:

10.0 kilohertz single component

Primary To Secondary Turn Ratio:

2 to 1 single component

Body Length:

Between 0.780 inches and 0.800 inches

Body Width:

Between 0.495 inches and 0.505 inches

Body Height:

Between 0.330 inches and 0.350 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Method:

Terminal single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Dc Resistance Rating In Ohms:

1.300 single component single primary

Test Data Document:

05869-732566-4 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

4 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0