

View Online at <https://aerobasegroup.com/nsn/5950-01-244-0514>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.590 inches single mounting facility single center group and 0.610 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.390 inches single mounting facility single center group and 0.410 inches single mounting facility single center group

**Inductance Rating:**

0.80 millihenries single component single primary and 1.20 millihenries single component single primary

**Frequency Rating:**

10.0 kilohertz single component

**Primary To Secondary Turn Ratio:**

2 to 1 single component

**Body Length:**

Between 0.780 inches and 0.800 inches

**Body Width:**

Between 0.495 inches and 0.505 inches

**Body Height:**

Between 0.330 inches and 0.350 inches

**Maximum Operating Temp:**

130.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Terminal single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Dc Resistance Rating In Ohms:**

1.300 single component single primary

**Test Data Document:**

05869-732566-4 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

4 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0