

View Online at <https://aerobasegroup.com/nsn/5950-01-244-6481>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.125 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.188 inches single mounting facility single center group

Mounting Slot Width:

0.219 inches single group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

50.0 volt-ampere single component

Body Length:

3.813 inches

Body Width:

3.813 inches

Body Height:

3.313 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Winding Operating Current:

218.0 milliamperes ac single component all secondary

Winding Power Rating:

25.0 volts-amperes single component all secondary

Winding Operating Voltage:

380.00 ac volts single component single primary and 440.00 ac volts single component single primary and 550.00 ac volts single component single primary and 600.00 ac volts single component single primary

Terminal Type And Quantity:

9 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0