NSN 5950-01-244-8369

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-244-8369

view Online at https://aerobasegroup.com/hsh/0550-01-244-0505
Reliability Indicator:
Not established
Turn Quantity:
385 single component single winding
Center To Center Distance Between Mounting Facilities Parallel To Length:
4.850 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.375 inches single mounting facility single center group
Inductance Type:
Fixed
Inductance Rating:
330.00 millihenries single component single winding
Frequency Rating:
60.0 hertz single component
Body Length:
5.700 inches
Body Width:
3.000 inches
Body Height:
2.600 inches
Maximum Operating Temp:
155.0 degrees celsius
Winding Quantity:
1 single component
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded hole single group
Rating Method:
Electrical single component single winding and winding turns single component single winding
Thread Size:
0.190 inches single group
Winding Conductor Size:
0.03196 inches american wire gage single component single winding
Winding Operating Current:
2.0 amperes dc single component single winding
Dc Resistance Rating In Ohms:

Feat

3.800 single component single winding

Criticality Code Justification:

NSN 5950-01-244-8369

Reactor - Page 2 of 2



Sı	oec	ial	Fe	atı	ur	es	:
----	-----	-----	----	-----	----	----	---

Item must comply with requirements of desc production standard no. L03543; for navy nuclear propulsion plant products only

Thread Series Designator:

Unf single group

Terminal Type And Quantity:

2 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0