

View Online at <https://aerobasegroup.com/nsn/5950-01-244-8376>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.562 inches single mounting facili type 1st center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.500 inches single mounting facili type 1st center group

**Frequency Rating:**

60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Maximum Transformer Power Rating:**

321.1 volt-ampere single component

**Winding Shielding Method:**

Internal shield brought out to terminal single component

**Body Length:**

5.250 inches

**Body Width:**

3.600 inches

**Body Height:**

5.220 inches

**Maximum Operating Temp:**

155.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 all groupings

**Mounting Method:**

Threaded hole all groupings

**Winding Function And Quantity:**

1 primary single component and 2 secondary single component

**Thread Size:**

0.190 inches all groupings

**Winding Operating Current:**

3.0 amperes ac single component 2nd secondary

**Winding Power Rating:**

220.0 volts-amperes single component 1st secondary

**Criticality Code Justification:**

Zzzy

**Winding Operating Voltage:**

33.70 ac volts single component 2nd secondary

**Special Features:**

Item must comply with requirements of defense supply center columbus production standard no. Lo3542

**Thread Series Designator:**

Unf all groupings

**Terminal Type And Quantity:**

1 terminal block w/screws

**Reference Number Differentiating Characteristics:**

Reference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing and testing specifications available at the dla icp

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0