

View Online at <https://aerobasegroup.com/nsn/5950-01-244-8376>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.562 inches single mounting facili type 1st center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches single mounting facili type 1st center group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

321.1 volt-ampere single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Length:

5.250 inches

Body Width:

3.600 inches

Body Height:

5.220 inches

Maximum Operating Temp:

155.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 all groupings

Mounting Method:

Threaded hole all groupings

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.190 inches all groupings

Winding Operating Current:

3.0 amperes ac single component 2nd secondary

Winding Power Rating:

220.0 volts-amperes single component 1st secondary

Criticality Code Justification:

Zzzy

Winding Operating Voltage:

33.70 ac volts single component 2nd secondary

Special Features:

Item must comply with requirements of defense supply center columbus production standard no. Lo3542

Thread Series Designator:

Unf all groupings

Terminal Type And Quantity:

1 terminal block w/screws

Reference Number Differentiating Characteristics:

Reference number differentiating material will be in accordance with naval inventory control point activity hx quality control. Manufacturing and testing specifications available at the dla icp

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0