## NSN 5950-01-245-1478

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-245-1478

## Reliability Indicator:

Not established

## Turn Quantity:

23 single component all winding

## Inductance Type:

Swinging

## Inductance Rating:

20.00 microhenries single component all winding and 40.00 microhenries single component all winding

## **Frequency Rating:**

10.0 kilohertz single component

## Body Length:

Between 1.480 inches and 1.520 inches

## Body Width:

Between 0.930 inches and 0.970 inches

## **Body Height:**

1.600 inches

## Maximum Operating Temp:

130.0 degrees celsius

### Winding Quantity:

2 single component

### Inclosure Type:

Fully enclosed

### Mounting Method:

Terminal single group

**Rating Method:** 

Electrical single component all winding and winding turns single component all winding

## Winding Conductor Size:

0.05082 inches american wire gage single component all winding

### Winding Operating Current:

0.0 amperes dc single component all winding and 15.0 amperes dc single component all winding

### Dc Resistance Rating In Ohms:

0.013 single component all winding

### Test Data Document:

56996-b4040030 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,

etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

### Terminal Type And Quantity:

4 pin

Shelf Life:

N/a

## Unit Of Measure:

---

#### Demilitarization:

No

# NSN 5950-01-245-1478

Reactor - Page 2 of 2

Fiig: A058b0

