NSN 5950-01-245-3415

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-245-3415

Reliability Indicator: Not established

Mounting Hole Diameter:

0.146 inches single group and 0.166 inches single group

Inductance Type:

Fixed

Inductance Rating:

2500.00 microhenries single component single winding

Frequency Rating:

10.0 kilohertz single component

Body Length:

Between 0.681 inches and 0.813 inches

Body Outside Diameter:

Between 1.345 inches and 1.405 inches

Maximum Operating Temp:

130.0 degrees celsius

Winding Quantity:

1 single component

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

1 single group

Mounting Method:

Unthreaded hole single group

Rating Method:

Electrical single component single winding

Winding Operating Current:

2.2 amperes dc single component single winding

Dc Resistance Rating In Ohms:

0.550 single component single winding

Test Data Document:

81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 pin

Specification Data:

81349-mil-t-27/289 government specification

Shelf Life:

N/a

- Unit Of Measure:
- --
- Demilitarization:

No

NSN 5950-01-245-3415

Reactor - Page 2 of 2

Fiig: A058b0

