

View Online at <https://aerobasegroup.com/nsn/5950-01-246-2832>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.745 inches single mounting facility single center group and 2.755 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.995 inches single mounting facility single center group and 1.005 inches single mounting facility single center group

Overall Height:

1.350 inches

Frequency Rating:

50.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

3.380 inches

Body Width:

1.400 inches

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 3 secondary single component

Winding Operating Current:

40.0 amperes dc single component 1st secondary

Winding Operating Voltage:

32.00 dc volts single component 2nd secondary

Special Features:

Pins 7 through 15 are internally connected together; pins 4a and 4b are internally connected; pins 6a and 6b are internally connected; center tap of first secondary winding has two windings connected to it

Terminal Type And Quantity:

17 pin and 6 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0