## NSN 5950-01-246-2832

Power Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-246-2832

Reliability Indicator:
Not established
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.745 inches single mounting facility single center group and 2.755 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.995 inches single mounting facility single center group and 1.005 inches single mounting facility single center group
Overall Height:
1.350 inches
Frequency Rating:
50.0 kilohertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Body Length:
3.380 inches
Body Width:
1.400 inches
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded hole single group
Winding Function And Quantity:
1 primary single component and 3 secondary single component
Winding Operating Current:
40.0 amperes dc single component 1st secondary
Winding Operating Voltage:
32.00 dc volts single component 2nd secondary
Special Features:
Pins 7 through 15 are internally connected together; pins 4a and 4b are internally connected; pins 6a and 6b are internally connected;
center tap of first secondary winding has two windings connected to it
Terminal Type And Quantity:
17 pin and 6 turret
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A058b0