

View Online at <https://aerobasegroup.com/nsn/5950-01-246-8711>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

0.300 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.100 inches single mounting facility single center group

**Impedance Rating In Ohms:**

10000.0 single component single secondary

**Frequency Rating:**

1.0 kilohertz single component

**Maximum Transformer Power Rating:**

50.0 milliwatts single component

**Primary To Secondary Turn Ratio:**

1 to 1 single component

**Body Length:**

Between 0.390 inches and 0.420 inches

**Body Width:**

Between 0.290 inches and 0.320 inches

**Body Height:**

Between 0.455 inches and 0.485 inches

**Maximum Operating Temp:**

105.0 degrees celsius

**End Application:**

4931-00-629-3541 test set, field

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Terminal single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Winding Operating Current:**

1.0 milliamperes dc single component single primary

**Precious Material And Location:**

Terminal surfaces gold

**Precious Material:**

Gold

**Terminal Type And Quantity:**

6 wire lead

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0