

View Online at <https://aerobasegroup.com/nsn/5950-01-246-8711>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.300 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.100 inches single mounting facility single center group

Impedance Rating In Ohms:

10000.0 single component single secondary

Frequency Rating:

1.0 kilohertz single component

Maximum Transformer Power Rating:

50.0 milliwatts single component

Primary To Secondary Turn Ratio:

1 to 1 single component

Body Length:

Between 0.390 inches and 0.420 inches

Body Width:

Between 0.290 inches and 0.320 inches

Body Height:

Between 0.455 inches and 0.485 inches

Maximum Operating Temp:

105.0 degrees celsius

End Application:

4931-00-629-3541 test set, field

Inclosure Type:

Fully enclosed

Mounting Method:

Terminal single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

1.0 milliamperes dc single component single primary

Precious Material And Location:

Terminal surfaces gold

Precious Material:

Gold

Terminal Type And Quantity:

6 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0