NSN 5950-01-247-8942

Power Transformer - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5950-01-247-8942

| Now Online at https://defobe | asegroup.com/nsi//3500-01-247-0542 |
|-------------------------------|---|
| Reliability Indicator: | |
| Not established | |
| Overall Height: | |
| 2.250 inches | |
| Input-output Phase Relation | onship: |
| Single phase to single phase | e single component |
| Maximum Transformer Por | wer Rating: |
| 550.0 volt-ampere single col | nponent |
| Body Length: | |
| Between 2.340 inches and 2 | 2.360 inches |
| Body Width: | |
| Between 2.240 inches and 2 | .260 inches |
| Body Height: | |
| Between 1.640 inches and 1 | .660 inches |
| Distance Between Mountir | ig Facility Centers: |
| 1.490 inches single mountir | ng facility single center group and 1.510 inches single mounting facility single center group |
| Inclosure Type: | |
| Fully enclosed | |
| Mounting Facility Quantity | : |
| 2 single group | |
| Mounting Method: | |
| Threaded stud single group | |
| Winding Function And Qua | antity: |
| 1 primary single component | and 1 secondary single component |
| Features Provided: | |
| Color coded lead and tinned | wire leads |
| Thread Size: | |
| 0.112 inches single group | |
| Winding Operating Curren | t: |
| 1.0 milliamperes dc single c | component single secondary and 50.0 milliamperes dc single component single secondary |
| Winding Operating Voltage | 2 : |
| 40.00 dc volts single compo | nent single secondary and 78.00 dc volts single component single secondary and 240.00 dc volts single |
| component single secondary | and 11.00 dc kilovolts single component single secondary |
| Thread Series Designator: | |
| Unc single group | |
| Terminal Type And Quanti | ty: |
| 7 wire lead and 1 wire lead w | v/tube cap |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| NI- | |

No

NSN 5950-01-247-8942

Power Transformer - Page 2 of 2

Fiig: A058b0

