

View Online at <https://aerobasegroup.com/nsn/5950-01-247-8973>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

4.200 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

4.400 inches single mounting facility single center group

**Impedance Rating In Ohms:**

865.0 single component 2nd secondary

**Pulse Repetition Rate:**

1.25 kilohertz single component

**Winding Shielding Method:**

Core grounded to secondary terminal single component

**Body Length:**

5.210 inches

**Body Width:**

5.120 inches

**Body Height:**

4.290 inches

**Maximum Operating Temp:**

155.0 degrees celsius

**End Application:**

Helicopter, carrier based asw; lamps mark iii, sh-60b helicopter

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Threaded hole single group

**Winding Function And Quantity:**

1 primary single component and 3 secondary single component

**Thread Size:**

0.138 inches single group

**Winding Operating Current:**

21.2 amperes ac single component 2nd secondary

**Criticality Code Justification:**

Feat

**Special Features:**

Weapon system essential

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

8 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0