

View Online at <https://aerobasegroup.com/nsn/5950-01-248-5938>

Reliability Indicator:

Not established

Turn Quantity:

25 3rd component 4th secondary

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.800 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.500 inches single mounting facility single center group

Inductance Rating:

90.00 microhenries 2nd component single winding and 3.10 millihenries 2nd component single winding

Frequency Rating:

400.0 hertz 1st component

Input-output Phase Relationship:

Single phase to single phase 4th component

Winding Shielding Method:

Internal shield grounded to terminal 3rd component

Body Length:

3.300 inches

Body Width:

2.010 inches

Body Height:

1.630 inches

End Application:

C5b acft; wsd: aircraft, galaxy c-5

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Rating Method:

Winding turns 4th component single secondary

Winding Function And Quantity:

1 primary 4th component and 1 secondary 4th component

Winding Conductor Size:

0.02535 inches american wire gage 4th component single primary

Winding Operating Current:

30.0 amperes dc 1st component single winding

Dc Resistance Rating In Ohms:

14.000 4th component single secondary

Criticality Code Justification:

Feat

Winding Operating Voltage:

7.48 ac volts 3rd component 3rd secondary

Special Features:

Weapon system essential

Terminal Type And Quantity:

28 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0