

View Online at <https://aerobasegroup.com/nsn/5950-01-249-5928>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Moisture resistant and fungus resistant and corrosion resistant and vibration resistant

Overall Length:

31.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

27.250 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

20.000 inches single mounting facility single center group

Overall Height:

28.250 inches

Overall Width:

28.000 inches

Mounting Hole Diameter:

0.625 inches single group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

25.6 amperes ac single component single secondary

Winding Power Rating:

200.0 kilovolt-amperes single component single secondary

Winding Operating Voltage:

7.80 ac kilovolts single component single secondary

Terminal Type And Quantity:

8 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0