NSN 5950-01-249-5928

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-249-5928

Reliability Indicator:
Not established
Hazardous Locations/environmental Protection:
Moisture resistant and fungus resistant and corrosion resistant and vibration resistant
Overall Length:
31.000 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
27.250 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
20.000 inches single mounting facility single center group
Overall Height:
28.250 inches
Overall Width:
28.000 inches
Mounting Hole Diameter:
0.625 inches single group
Frequency Rating:
50.0 hertz single component or 60.0 hertz single component
Input-output Phase Relationship:
Single phase to single phase single component
Inclosure Type:
Open
Mounting Facility Quantity:
4 single group
Mounting Method:
Unthreaded hole single group
Winding Function And Quantity:
1 primary single component and 1 secondary single component
Winding Operating Current:
25.6 amperes ac single component single secondary
Winding Power Rating:
200.0 kilovolt-amperes single component single secondary
Winding Operating Voltage:
7.80 ac kilovolts single component single secondary
Terminal Type And Quantity:
8 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5950-01-249-5928

Power Transformer - Page 2 of 2



Fiig:

A058b0