

View Online at <https://aerobasegroup.com/nsn/5950-01-249-5929>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Corrosion resistant and fungus resistant and humidity resistant and vibration resistant

Overall Length:

11.000 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

8.000 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

6.370 inches single mounting facility single center group

Overall Height:

14.500 inches

Overall Width:

7.620 inches

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Flange single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

21.0 amperes ac single component single primary

Winding Power Rating:

10.0 kilovolt-amperes single component single secondary

Winding Operating Voltage:

456.00 ac volts single component single primary and 468.00 ac volts single component single primary and 480.00 ac volts single component single primary and 492.00 ac volts single component single primary and 504.00 ac volts single component single primary

Special Features:

Mounting flange has drilled or slotted holes

Terminal Type And Quantity:

1 terminal block w/screws

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0