

View Online at <https://aerobasegroup.com/nsn/5950-01-249-5929>

**Reliability Indicator:**

Not established

**Hazardous Locations/environmental Protection:**

Corrosion resistant and fungus resistant and humidity resistant and vibration resistant

**Overall Length:**

11.000 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

8.000 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

6.370 inches single mounting facility single center group

**Overall Height:**

14.500 inches

**Overall Width:**

7.620 inches

**Frequency Rating:**

50.0 hertz single component or 60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Inclosure Type:**

Open

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Flange single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Winding Operating Current:**

21.0 amperes ac single component single primary

**Winding Power Rating:**

10.0 kilovolt-amperes single component single secondary

**Winding Operating Voltage:**

456.00 ac volts single component single primary and 468.00 ac volts single component single primary and 480.00 ac volts single component single primary and 492.00 ac volts single component single primary and 504.00 ac volts single component single primary

**Special Features:**

Mounting flange has drilled or slotted holes

**Terminal Type And Quantity:**

1 terminal block w/screws

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0