NSN 5950-01-249-7066

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-249-7066

Reliability Indicator:
Not established
Overall Length:
2.340 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
1.906 inches single mounting facility single center group
Center To Center Distance Between Mounting Facilities Parallel To Width:
1.812 inches single mounting facility single center group
Overall Width:
1.120 inches
Inductance Type:
Fixed
Inductance Rating:
1.00 millihenries single component single winding
Frequency Rating:
20.0 kilohertz single component
Body Height:
2.500 inches
Maximum Operating Temp:
130.0 degrees celsius
Winding Quantity:
1 single component
Inclosure Type:
Fully enclosed
Mounting Facility Quantity:
4 single group
Mounting Method:
Threaded hole single group
Rating Method:
Electrical single component single winding
Thread Size:
0.138 inches single group
Winding Operating Current:
3.0 amperes dc single component single winding
Dc Resistance Rating In Ohms:
0.124 single component single winding
Test Data Document:
81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:

2 pin

Unc single group

Terminal Type And Quantity:

NSN 5950-01-249-7066

Reactor - Page 2 of 2



Spec	ifica	ation	Data:
------	-------	-------	-------

81349-mil-t-27/123 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0