## NSN 5950-01-250-2549

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-250-2549

| Reliability Indicator:   |
|--|
| Not established  |
| Turn Quantity:   |
| 90 single component all winding  |
| Inductance Type:   |
| Fixed  |
| Inductance Rating:   |
| 4.40 millihenries single component 2nd winding   |
| Frequency Rating:  |
| 20.0 kilohertz single component  |
| Body Length:   |
| 0.650 inches   |
| Body Width:  |
| 0.900 inches   |
| Body Height:   |
| 1.100 inches   |
| Maximum Operating Temp:  |
| 85.0 degrees celsius   |
| End Application:   |
| Wsd: aircraft, galaxy c-5  |
| Winding Quantity:  |
| 2 single component   |
| Inclosure Type:  |
| Fully enclosed   |
| Mounting Method:   |
| Terminal single group  |
| Rating Method:   |
| Electrical single component all winding and winding turns single component all winding |
| Winding Conductor Size:  |
| 0.03196 inches american wire gage single component all winding                         |
| Winding Operating Current:   |
| 0.55 amperes dc single component 2nd winding   |
| Dc Resistance Rating In Ohms:  |
| 0.460 single component 2nd winding   |
| Criticality Code Justification:  |
| Feat   |
| Special Features:  |
| Weapon system essential  |
| Terminal Type And Quantity:  |
| 4 wire lead  |
| Shelf Life:  |
| N/a  |

## NSN 5950-01-250-2549

Reactor - Page 2 of 2



| ı | 1 | n | iŧ | <b>1</b> | : N/ | lea |     |    | _ |   |
|---|---|---|----|----------|------|-----|-----|----|---|---|
| ı | u | n | IT | OI       | ١V   | ıea | เรเ | JI | е | : |

--

Demilitarization:

No

Fiig:

A058b0