

View Online at <https://aerobasegroup.com/nsn/5950-01-250-2553>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.187 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.187 inches single mounting facility single center group

Frequency Rating:

2.05 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

0.6 volt-ampere single component

Winding Shielding Method:

Internal shield grounded to inclosure single component

Body Length:

1.540 inches

Body Width:

1.540 inches

Body Height:

1.680 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded stud single group

Winding Function And Quantity:

2 primary single component and 2 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

20.0 milliamperes ac single component 2nd primary

Winding Power Rating:

0.4 volts-amperes single component 1st primary

Winding Operating Voltage:

80.00 ac volts single component 1st secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

8 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0