

View Online at <https://aerobasegroup.com/nsn/5950-01-250-4770>

Reliability Indicator:

Not established

Hazardous Locations/environmental Protection:

Vibration resistant

Overall Length:

0.500 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.400 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.100 inches single mounting facility single center group

Overall Width:

0.350 inches

Impedance Rating In Ohms:

3000.0 single component single primary

Frequency Rating:

75.0 kilohertz single component and 1.0 megahertz single component

Primary To Secondary Turn Ratio:

1 to 1 single component

Body Height:

0.250 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Method:

Terminal single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Dc Resistance Rating In Ohms:

2.800 single component single secondary

Test Data Document:

81349-mil-t-21038 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

6 pin

Specification Data:

81349-mil-t-21038/27 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0