NSN 5950-01-251-5060

Radio Frequency Coil - Page 1 of 2



reflect specification type data in specification

View Online at https://aeroba m/psp/5950-01-251-5060

View Onl	line at https://aerobasegroup.com/nsn/5950-01-251-5060
Reliabili	ty Indicator:
Not estat	blished
Inductar	nce Rating:
5.60 micr	rohenries single component single winding
Coil For	m Type:
Solid sing	gle component
Core Co	nstruction:
S0lid sing	gle component
Body Le	ngth:
Between	0.240 inches and 0.260 inches
Overall [Diameter:
Between	0.085 inches and 0.105 inches
Maximur	m Operating Temp:
105.0 de	grees celsius
Inclosur	е Туре:
Fully enc	closed
Mounting	g Method:
Terminal	single group
Rating N	lethod:
Electrical	I single component single winding
Winding	Conductor Size:
0.01594	inches american wire gage single component single winding
Winding	Operating Current:
124.0 mil	lliamperes dc single component single winding
Dc Resis	stance Rating In Ohms:
2.900 sin	ngle component single winding
Quality F	Factor:
54 single	e component single winding
Special I	Features:
Magnetic	cally shielded
Test Dat	a Document:
81349-m	il-c-15305 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specifica
format; e	excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environm	nental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Termina	I Type And Quantity:
2 wire lea	ad
Specifica	ation Data:
96906-m	s21426 government standard
Shelf Lif	e:
N/a	
Unit Of M	Measure:

Unit Of Measure:

- Demilitarization:
- No

NSN 5950-01-251-5060

Radio Frequency Coil - Page 2 of 2

Fiig: A058b0

