

View Online at <https://aerobasegroup.com/nsn/5950-01-253-2794>

Reliability Indicator:

Not established

Turn Quantity:

2 1st component 3rd secondary

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.700 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.700 inches single mounting facility single center group

Frequency Rating:

19.0 kilohertz 1st component

Input-output Phase Relationship:

Single phase to single phase 2nd component

Body Length:

1.080 inches

Body Width:

1.080 inches

Body Height:

1.100 inches

End Application:

F-16 aircraft

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 single group

Mounting Method:

Threaded hole single group

Rating Method:

Winding turns 2nd component single secondary

Winding Function And Quantity:

1 primary 2nd component and 1 secondary 2nd component

Thread Size:

0.112 inches single group

Winding Conductor Size:

0.05082 inches american wire gage 2nd component single primary

Dc Resistance Rating In Ohms:

16.000 2nd component single secondary

Criticality Code Justification:

Feat

Winding Operating Voltage:

15.00 ac volts 1st component single primary

Special Features:

Weapon system essential

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0