

View Online at <https://aerobasegroup.com/nsn/5950-01-254-0548>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.600 inches single mounting facility single center group and 1.640 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.480 inches single mounting facility single center group and 1.520 inches single mounting facility single center group

Mounting Slot Width:

0.140 inches single group and 0.180 inches single group

Frequency Rating:

47.0 hertz single component and 440.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Length:

2.140 inches

Body Width:

2.020 inches

Body Height:

2.500 inches

Maximum Operating Temp:

105.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

400.0 milliamperes ac single component single secondary

Winding Power Rating:

11.2 volts-amperes single component single secondary

Winding Operating Voltage:

28.00 ac pounds per hour wet single component single secondary

Test Data Document:

97942-147c547 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

4 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0