

View Online at <https://aerobasegroup.com/nsn/5950-01-254-0548>

**Reliability Indicator:**

Not established

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

1.600 inches single mounting facility single center group and 1.640 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

1.480 inches single mounting facility single center group and 1.520 inches single mounting facility single center group

**Mounting Slot Width:**

0.140 inches single group and 0.180 inches single group

**Frequency Rating:**

47.0 hertz single component and 440.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Body Length:**

2.140 inches

**Body Width:**

2.020 inches

**Body Height:**

2.500 inches

**Maximum Operating Temp:**

105.0 degrees celsius

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Slot single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Winding Operating Current:**

400.0 milliamperes ac single component single secondary

**Winding Power Rating:**

11.2 volts-amperes single component single secondary

**Winding Operating Voltage:**

28.00 ac pounds per hour wet single component single secondary

**Test Data Document:**

97942-147c547 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

4 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0