

View Online at <https://aerobasegroup.com/nsn/5950-01-254-2151>

Reliability Indicator:

Not established

Mounting Hole Diameter:

0.187 inches 1st group

Mounting Slot Width:

0.187 inches 3rd group

Frequency Rating:

10.0 kilohertz all components

Input-output Phase Relationship:

Single phase to single phase all components

Winding Shielding Method:

Internal shield brought out to terminal 2nd component

Body Length:

4.750 inches

Body Width:

2.812 inches

Body Height:

3.570 inches

Distance Between Mounting Facility Centers:

5.375 inches 1st mounting facility single center group

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 all groupings

Mounting Method:

Unthreaded hole 1st group

Rating Method:

Electrical all components all primary

Winding Function And Quantity:

2 primary 1st component and 3 secondary 1st component

Thread Size:

0.164 inches 2nd group

Winding Operating Current:

30.0 milliamperes ac 1st component 4th secondary

Winding Operating Voltage:

6.01 ac volts 2nd component 4th secondary

Thread Series Designator:

Unc 2nd group

Terminal Type And Quantity:

2 connector, receptacle

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0