

View Online at <https://aerobasegroup.com/nsn/5950-01-254-5248>

Reliability Indicator:

Not established

Center To Center Distance Between Mounting Facilities Parallel To Length:

1.490 inches single mounting facility single center group and 1.510 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.490 inches single mounting facility single center group and 1.510 inches single mounting facility single center group

Frequency Rating:

1.5 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Transformer Power Rating:

2.3 volt-ampere single component

Body Length:

2.000 inches

Body Width:

2.000 inches

Body Height:

2.000 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Hermetically sealed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 2 secondary single component

Thread Size:

0.164 inches single group

Winding Operating Current:

76.7 milliamperes ac single component single primary

Winding Operating Voltage:

7.585 ac volts single component 2nd secondary and 19.22 ac volts single component 2nd secondary and 42.62 ac volts single component 2nd secondary and 54.255 ac volts single component 2nd secondary and 61.84 ac volts single component 2nd secondary

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

13 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0