NSN 5950-01-255-3948

Power Transformer - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5950-01-255-3948 |
|--|
| Reliability Indicator: |
| Not established |
| Hazardous Locations/environmental Protection: |
| Vibration resistant |
| Overall Length: |
| 1.090 inches |
| Overall Height: |
| 1.030 inches |
| Overall Width: |
| 1.090 inches |
| Frequency Rating: |
| 400.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Maximum Transformer Power Rating: |
| 6.0 volt-ampere single component |
| Maximum Operating Temp: |
| 130.0 degrees celsius |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 1 single group |
| Mounting Method: |
| Threaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 1 secondary single component |
| Thread Size: |
| 0.138 inches single group |
| Winding Operating Current: |
| 182.0 milliamperes ac single component single secondary |
| Winding Operating Voltage: |
| 33.00 ac volts single component single secondary |
| Test Data Document: |
| 81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Thread Series Designator: |
| Unc single group |
| Terminal Type And Quantity: |
| 5 pin |
| Specification Data: |

N/a

Shelf Life:

81349-mil-t-27/41 government specification

NSN 5950-01-255-3948

Power Transformer - Page 2 of 2



| | Of | | | |
|--|----|--|--|--|

--

Demilitarization:

No

Fiig:

A058b0