

View Online at <https://aerobasegroup.com/nsn/5950-01-256-0102>

Reliability Indicator:

Not established

Overall Length:

3.360 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.500 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

1.750 inches single mounting facility single center group

Overall Height:

3.060 inches

Mounting Hole Diameter:

0.166 inches single group and 0.218 inches single group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Body Width:

1.560 inches

Maximum Operating Temp:

85.0 degrees celsius

End Application:

Pstrategic sealift conversion ships class, waters class tags-45, victorious class t-agos 19, hayes class t-ag 195, bob hope class t-akr 300, t-akr 310 class, whidbey island class lsd, usns henery j. Kaiser class tao.

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Unthreaded hole single group

Winding Function And Quantity:

2 primary single component and 4 secondary single component

Features Provided:

Color coded lead

Winding Operating Current:

500.0 milliamperes dc single component 2nd secondary

Criticality Code Justification:

Feat

Winding Operating Voltage:

20.00 ac pounds per hour wet single component 2nd secondary

Special Features:

Weapon system essential

Terminal Type And Quantity:

12 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0