

View Online at <https://aerobasegroup.com/nsn/5950-01-256-0221>

**Reliability Indicator:**

Not established

**Overall Length:**

1.313 inches

**Frequency Rating:**

7.0 kilohertz single component and 10.0 kilohertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Winding Shielding Method:**

Internal shield brought out to terminal single component

**Body Outside Diameter:**

2.000 inches

**Maximum Operating Temp:**

130.0 degrees celsius

**End Application:**

1430-01-181-5884 battery command

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

1 single group

**Mounting Method:**

Threaded hole single group

**Winding Function And Quantity:**

1 primary single component and 8 secondary single component

**Thread Size:**

0.138 inches single group

**Winding Operating Current:**

769.2 milliamperes ac single component 4th secondary

**Winding Operating Voltage:**

9.10 ac volts single component 4th secondary

**Special Features:**

One primary winding; eight secondary windings

**Test Data Document:**

18876-11568074 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:**

Unc single group

**Terminal Type And Quantity:**

20 turret

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0