

View Online at <https://aerobasegroup.com/nsn/5950-01-256-0221>

Reliability Indicator:

Not established

Overall Length:

1.313 inches

Frequency Rating:

7.0 kilohertz single component and 10.0 kilohertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Winding Shielding Method:

Internal shield brought out to terminal single component

Body Outside Diameter:

2.000 inches

Maximum Operating Temp:

130.0 degrees celsius

End Application:

1430-01-181-5884 battery command

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

1 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 8 secondary single component

Thread Size:

0.138 inches single group

Winding Operating Current:

769.2 milliamperes ac single component 4th secondary

Winding Operating Voltage:

9.10 ac volts single component 4th secondary

Special Features:

One primary winding; eight secondary windings

Test Data Document:

18876-11568074 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

20 turret

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0